

### AMENDMENTS TO THE CLAIMS

The following listing of claims replaces all prior listings in this application.

1-14. (Canceled) A method for preventing freezing at an outlet of a fire extinguisher, wherein said fire extinguisher contains fire extinguisher fluid, said method comprising:

15. (Currently amended) An apparatus for preventing freezing at an outlet of a fire extinguisher, said apparatus comprising:

a fire extinguisher bottle; and

a container in the bottle having walls with a plurality of openings therein sized to confine a drying agent in the container but to permit fire extinguisher fluid to enter through the openings into the container, said container being open to the interior of the bottle so that as soon as fire extinguisher fluid is introduced into the bottle, the fluid comes into contact with the drying agent and contacts the drying agent substantially continuously,

wherein said container when positioned in said bottle remains unattached to the container so as to be readily removable, and said container includes flexible structure attached to the container that spaces the container from interior walls of the bottle and restricts movement of the container within the bottle when the bottle is subjected to movement.

16. (Canceled)

17. (Original) The apparatus of Claim 15, wherein said removable container is generally tubular shaped.

18. (Original) The apparatus of Claim 15, wherein said removable container is made, at least in part, of mesh.

19. (Original) The apparatus of Claim 18, wherein the mesh is made of metal.

20. (Original) The apparatus of Claim 19, wherein the mesh is made of stainless steel.

21. (Currently amended) The apparatus of Claim 15, wherein the flexible structure includes including at least one flexible projection on the exterior of said container ~~to space the container from the outlet.~~

22. (Previously presented) An apparatus for preventing freezing at an outlet of a fire extinguisher, said apparatus comprising:

a fire extinguisher bottle;

a container having a plurality of openings in the container, wherein the container contains a drying agent;

wherein said container is removable from inside said fire extinguisher bottle; and said container further comprises at least one flexible projection on said removable container to prevent said removable container from plugging an outlet of the fire extinguisher.

23. (Previously presented) An apparatus for preventing freezing at an outlet of a fire extinguisher, said apparatus comprising:

a fire extinguisher bottle;

a container having a plurality of openings in the container, wherein the container contains a drying agent;

wherein said container is removable from inside said fire extinguisher bottle; and said container further comprises at least one flexible projection comprising a flexible wire having at least two ends attached to said removable container, thereby forming a flexible projection.

24. (Original) The apparatus of Claim 15, wherein said removable container is removable from said fire extinguisher bottle through an outlet of said fire extinguisher bottle.

25. (Original) The apparatus of Claim 15, wherein said drying agent is a molecular sieve.

26. (Original) The apparatus of Claim 25, wherein said molecular sieve is 3A or 4A molecular sieve.

27. (Original) The apparatus of Claim 23, wherein said container is generally tubular shaped, and said wire extends beyond opposite ends of the tube so that the tube is blocked by the wire from entering an outlet from the bottle.

28. (Canceled)

29. (Previously presented) The apparatus of ~~Claim 28~~ Claim 15, wherein said flexible structure is configured to be collapsible or compressible to facilitate insertion or removal

of the container from the bottle and is restorable within the bottle to space the container from the interior walls of the bottle.

30. (Previously presented) An apparatus for preventing freezing at an outlet of a fire extinguisher, said apparatus comprising:

a container having self-supporting walls with a plurality of openings formed therein that are sized to confine a drying agent in the form of pellets or other small particles, the openings being sufficiently large to allow fire extinguisher fluid to readily flow into the container when the container is positioned in a fire extinguisher bottle; and

means extending outwardly from the exterior of the container for spacing the container from interior walls of a fire extinguisher bottle, but open to the bottle interior.

31. (Previously presented) The apparatus of Claim 30 wherein said spacing means is collapsible towards the container to facilitate insertion and removal of the container from the bottle.

32. (Previously presented) The apparatus of Claim 30 wherein said spacing means comprises a pair of wire loops with each loop having ends secured to opposite ends of a container with the loops extending outwardly from side walls of the container on opposite sides of the container, said wire loops being bendable or collapsible towards the container to facilitate insertion or removal of the container from the bottle.

33. (Previously presented) The apparatus of Claim 30 wherein said spacing means comprises a layer of sponge-like foam attached to the exterior of the container.

34. (Previously presented) The apparatus of Claim 30 wherein said container comprises a tubular shape and metal mesh walls.